

3DP-PLA+1.75-02-GR

PLA-PLUS filament, grey, 1.75 mm, 1 kg

MUCH BETTER HARDNESS THAN NORMAL PLA

- THE HARDNESS IS PRACTICALLY EQUAL TO ABS
- ENVIRONMENTALLY FRIENDLY AND WITHOUT THE SMELL OF ABS
- VERSATILE & EASY TO USE
- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment.
- PLA-plus plastic variant has a bit higher hardness and toughness than regular PLA, and is more environmental friendly, also it is not so easy warped while printing.



Specifications

Material: PLA+, 1.75 mm diameter Weight: 1 kg/spool (2.2 lbs) Length: approx. 330 m Density at 21.5 °C: 1.25 g/cm3 Melt Flow Index at g / 10 min 190 °C / 5 kg: 5

Malt Dailer 105 0C 225 0C

Melt Point: 195 °C 235 °C

Heat-Deflection-Temperature: 47 $^{\circ}\text{C}$ Yield Strength at 5 mm / min: 72 MPa

Impact Strength: 12 KJ/m Ensile Break: 30 %

Diameter: 1.75 mm ± 0.05 mm

Spool dimensions: 200 mm (diameter) x 67 mm (height) x 53 mm (central

hole

Features

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Q'ty in crtn, pcs
Crtn volume, CUM
Crtn weight, kgs
Individual package size LxWxH:
Carton size LxWxH:
Country of origin
Barcode
Customs code

8 0.036 10.75 210x85x210 mm 445x445x180 mm CN 8716309103695 3916909000

System requirements

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Certificates





