gembird°

3DP-PLA+1.75-02-0 PLA-PLUS filament, orange, 1.75 mm, 1 kg

MUCH BETTER HARDNESS THAN NORMAL PLA

- THE HARDNESS IS PRACTICALLY EQUAL TO ABS
- ENVIRONMENTALLY FRIENDLY AND WITHOUT THE SMELL OF ABS
- VERSATILE & EASY TO USE
- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment.
- ⁻ PLA-plus plastic variant has a bit higher hardness and toughness than regular PLA, and is more environmental friendly, also it is not so easy warped while printing.



Specifications

Material: PLA+, 1.75 mm diameter Weight: 1 kg/spool (2.2 lbs) Length: approx. 330 m Density at 21.5 °C: 1.25 g/cm3 Melt Flow Index at g / 10 min 190 °C / 5 kg: 5 Melt Point: 195 °C 235 °C Heat-Deflection-Temperature: 47 °C Yield Strength at 5 mm / min: 72 MPa Impact Strength: 12 KJ/m Ensile Break: 30 % Diameter: 1.75 mm ± 0.05 mm Spool dimensions: 200 mm (diameter) x 67 mm (height) x 53 mm (central hole)

Features

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 8 0.036 10.75 210x85x210 mm 445x445x180 mm CN 8716309103701 3916909000

System requirements

A 3D printer with 1.75 mm extruder of temperature around 200 $^{\rm o}{\rm C}$, suitable for PLA filament

Certificates



Copyright © 2009–2024, Gembird Software Ltd.

Gembird Europe B.V. Wittevrouwen 56, 1358CD Almere, The Netherlands. Phone: +31-36-5211588