PCMCIA-SATA2
Serial ATA CardBus PCMCIA card 2 SATA ports

- Serial ATA 2 ports CardBus PCMCIA card

Specifications

Supports Spread Spectrum in receiver
Independent 256-byte FIFOs (32 bit x 64 deep) per Serial ATA channel for host reads and writes
Drivers for Windows 98, Windows Millennium, Windows NT 4.0, Windows 2000 and XP

Features

- Supports High Speed Transfer Rate 1,500Mbps
- Breaks Space-Limit to Support HDD larger than 137GB
- Special enhanced SATA shell connectors for Mobile HDD, Mobile

- CD-ROM, Mobile DVD, Mobile CD-RW
- Dual high speed Serial ATA interface ports, each supporting 1st generation Serial ATA data rates 1.5Gb/s
- Fully compliant with Serial ATA 1.0 specifications
- Supports Spread Spectrum in receiver
- Independent 256-byte FIFOs (32 bit x 64 deep) per Serial ATA channel for host reads and writes

Packaging

Q'ty in crtn, pcs	100
Crtn volume, CUM	0.119
Crtn weight, kgs	11.2
Individual package size LxWxH:	150x190x35 mm
Carton size LxWxH:	780x400x380 mm
Country of origin	CN
Barcode	8716309035385
Customs code	8471800000

Certificates