

UPS with AVR, 650 VA

UPS-PC-652A

ULTIMATE DEFENCE

- Up to 20 minutes backup power for your PC
- Prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for use at home or small office



Features

- Uninterruptable 650 VA power supply for PC's
- Automatic AC voltage regulation (AVR)
- Surge protected output sockets protect your equipment against harmful power surges, lightning strikes and short-circuits
- Audible and visual alarms
- LED status indication
- Internal battery with overcharge and over-discharge protection

Packaging

Q'ty in crtn, pcs	3
Crtn volume, CUM	0.04158
Crtn weight, kgs	17.8
Individual package size LxWxH:	375x145x230 mm
Carton size LxWxH:	450x385x240 mm
Country of origin	CN
Barcode	8716309047807
Customs code	8504408590

Package contents

UPS
Power cord
Spare fuse

Certificates



Specifications

UPS type: line interactive
Input: AC 162 295 V, 50 Hz / 60 Hz \pm 10 %
Output: AC 188 254 V, 50 Hz / 60 Hz \pm 0.5 % (on battery)
Waveform: sine wave (AC mains), simulated sine wave (battery)

Temperature compensation: -20mV/1 °C (per cell)
Switching time: no more than 10 ms
Backup time: (8 to 20) min (depending on connected load)
Battery: sealed lead-acid 12 V / 7Ah
Charge time: up to 12 hours
Sockets: 1x C14 input, 2x C13 output
Operating conditions: 0°C to 40°C, at 20% to 90% humidity (RH non-condensing)
Power: 650 VA (390 W)
Dimensions: 320 mm x 160 mm x 95 mm
Product weight: 4.8 kg
"Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.