

850VA UPS with AVR, advanced

UPS-PC-850AP

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use





Specifications

UPS type: line interactive

Input: AC 162 295 V, 50 Hz / 60 Hz \pm 10 %

Output: AC 188 254 V, 50 Hz / 60 Hz \pm 0.5 % (on battery)

Waveform: sine wave (AC mains), simulated sine wave (battery)

Temperature compensation: -20mV/1 $^{\circ}$ C (per cell)

Switching time: no more than 10 \mbox{ms}

Backup time: 8...20 mins (depends on the load) Battery: sealed lead-acid 12V/7Ah x 1 pc

Charge time: up to 12 hours

Sockets: 1x C14 input, 2x C13 outputs; USB-BF connector

Operating conditions: 0 °C~40 °C, at humidity 20~90 %RH non condensing

Power: 850 VA (520 W)

Dimensions: 340 x 95 x 165 mm

Product weight: 7 kg "Cold-start" function

Features

- Uninterruptable 850 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 3 0.053475 21 375x145x230 mm 460x375x310 mm CN 8716309057066 8504408590

Package contents

UPS Power cord USB cable Software CD Spare fuse

Certificates









Copyright © 2009-2024, Gembird Software Ltd.

Software is compatible with Windows 7, Windows 2008 server, Windows

System requirements

8/10

In order to work correctly, the connected load should be at least 5% of the