HDMI splitter, 8 ports

DSP-8PH4-03

PERFECT CONNECTION

- Sends a single HDMI signal to 8 displays
- Signal amplifier Improves signal quality
- Perfect for home theatres, classand conference rooms



Features

- Sends a single HDMI signal to 8 separate monitors, projectors or TV's
- The digital 340 MHz bandwidth amplifier increases the transmission distance
- Supports 3D video

Specifications

Ports: one input receptacle, 8 output HDMI output receptacles, 19 pin (A)

Interface standard: HDMI + HDCP v.1.4b (compatible with all HDMI versions)

Video formats: HDMI up to 38402160/30Hz, 8/10/12 bit color; audio DTS-HD/ Dolby-trueHD/DTS/Dolby-AC3/DSD
Video amplifier: up to 340 MHz bandwidth, 3.2 Gbps
Input cable distance: (1080p resolution) 15m, (4K resolution), 12m AWG26 HDMI cable
Output cable distance: (1080p resolution) 25m, (4K resolution), 15m AWG26 HDMI cable
Shell material: steel
Power adapter: 5 V DC, 3 A
Power consumption: up to 1.6 A, 5 V DC
Dimensions: 276 x 136 x 24 mm
Net weight: 0.66 kg

Packaging

Q'ty in crtn, pcs	10
Crtn volume, CUM	0.042112
Crtn weight, kgs	10.82
Individual package size LxWxH:	320x220x60 mm
Carton size LxWxH:	470x320x280 mm
Country of origin	CN
Barcode	8716309092494
Customs code	8517620000

Package contents

Splitter
Power adapter
User manual

Certificates

Copyright © 2009–2022, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.cablexpert.com | postmaster@cablexpert.com