

## UPS with AVR, 650 VA, 6 Schuko sockets, USB

EG-UPS-DT650U-01

### ULTIMATE DEFENCE

- Table top design
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



### Features

- Uninterruptable 650 VA power supply with modified sine wave output
- Automatic AC voltage regulation (AVR)
- USB interface
- Intelligent surge-, overload and short-circuit protection
- UPS battery backup
- Audible and visual alarms
- LED status indication
- Intelligent battery management with overcharge and over-discharge protection
- Wall mountable

### Packaging

Q'ty in crtn, pcs	3
Crtn volume, CUM	0.0388125
Crtn weight, kgs	15.82
Individual package size LxWxH:	330x150x240 mm
Carton size LxWxH:	450x345x250 mm
Country of origin	CN
Barcode	8716309098922
Customs code	8504408490

### Package contents

UPS  
Power cord  
User manual

### Specifications

Type: line interactive  
Waveform: sine wave (AC mains), modified (square) sine wave (battery)  
Input: 220 V AC  $\pm$  25%, 50 / 60 Hz  $\pm$  10%  
Output: 220 V AC  $\pm$  10%, 50 / 60 Hz  $\pm$  1% (220 V AC  $\pm$  5 % at inverter mode)  
Switching time: less than 10 ms  
Backup time: 10...30 mins (depends on the load)  
Battery: sealed lead-acid 12 V DC / 7Ah  
Charge time: up to 8 hours  
Sockets: 1 x C13 (input), cable CEE 7/7P, 6 x Schuko (output)

### System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

### Certificates

