

Online UPS, 3000 VA

EG-UPS0-3000

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Features

- Online type UPS: double voltage conversion without switching the power
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 1 |
| Crtn volume, CUM | 0.0602 |
| Crtn weight, kgs | 26.74 |
| Individual package size LxWxH: | 500x280x430 mm |
| Carton size LxWxH: | 500x280x430 mm |
| Country of origin | CN |
| Barcode | 8716309124799 |
| Customs code | 8504408590 |

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificates



Specifications

UPS type: online, pure sine wave
Input: 220V AC \pm 25%, 50Hz / 60Hz \pm 10%
Output: 220V AC \pm 1%, 50Hz / 60Hz \pm 0.5% (on battery)
Output power factor: 0.9
Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: zero
Backup time: 8...20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.35 kg x 6 pcs (72 VDC)
Charge time: 90% capacity restored in 3 hours
External battery connectors: yes
Sockets: input IEC C14, outputs: 2x Schuko sockets + 3x IEC sockets

Interface communication: USB; optional slots: RS485 / dry contacts / SNMP

Operating conditions: 0°C-40°C, at humidity 10-90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
Power: 3000 VA (2700 W)
Dimensions: 191 x 419 x 335 mm
Product weight: 24.3 kg
"Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.