

UPS "Desktop", 600 VA

EG-UPS-3SDT600-01

ULTIMATE DEFENCE

- Table top design
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 600 VA power supply with modified sine wave output
- Automatic AC voltage regulation (AVR)
- Intelligent surge-, overload and short-circuit protection on all 3 sockets
- UPS battery backup on 3 sockets
- Audible and visual alarms
- LED status indication
- Intelligent battery management with overcharge and over-discharge protection
- Wall mountable

Packaging

Q'ty in crtn, pcs	4
Crtn volume, CUM	0.039251432
Crtn weight, kgs	19.56
Individual package size LxWxH:	329x150x240 mm
Carton size LxWxH:	451x344x253 mm
Country of origin	CN
Barcode	8716309126366
Customs code	8504408590

Package contents

UPS
User manual

Certificates



Specifications

Type: line interactive
 Waveform: sine wave (AC mains), modified (square) sine wave (battery)
 Input: 220 V AC \pm 25%, 50 / 60 Hz \pm 10%
 Output: 220 V AC \pm 10%, 50 / 60 Hz \pm 1% (220 V AC \pm 5 % at inverter mode)
 Switching time: less than 12 ms
 Backup time: 10...30 mins (depends on the load)
 Battery: sealed lead-acid 12 V DC / 7Ah x 1 pc
 Charge time: up to 8 hours
 Input: built-in Schuko plug cable, 1.2 m
 Sockets: 3 pcs x Schuko output
 Operating conditions: 0°C~40°C, at humidity 5~90%RH non condensing
 Power: 600 VA (360 W)
 Noise: < 45 dB at 1 m distance
 Dimensions: 175 x 255 x 93 mm
 Product weight: 4.2 kg
 "Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.