

## Online rack UPS, 2000 VA

EG-UPSO-RACK-2000

### ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



### Features

- Online type UPS: double voltage conversion without switching the power
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

### Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.07142334
Crtn weight, kgs	21.19
Individual package size LxWxH:	652x545x201 mm
Carton size LxWxH:	652x545x201 mm
Country of origin	CN
Barcode	8716309126526
Customs code	8504408590

### Package contents

UPS  
Power cord  
USB cable  
Software CD  
Spare fuse

### Certificates



### Specifications

UPS type: online, pure sine wave  
 Input: 220V AC  $\pm$  25%, 50Hz / 60Hz  $\pm$  10%  
 Output: 220V AC  $\pm$  1%, 50Hz / 60Hz  $\pm$  0.5% (on battery)  
 Output power factor: > 0.99  
 Inverter output efficiency (resistive load): 85%, any load type is allowed  
 Switching time: zero  
 Backup time: 8...20 mins (depends on the load)  
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.35 kg x 4 pcs, 48VDC  
 Charge time: 90% capacity restored in 3 hours  
 External battery connectors: yes  
 Sockets: input IEC C14, outputs: 8x IEC sockets  
 Interface communication: USB; optional slots: RS485 / dry contacts / SNMP  
 Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing  
 Noise: < 45 dB (at 1 meter distance)  
 Power: 2000 VA (1800 W)  
 Dimensions: 440 x 528 x 88 mm  
 Product weight: 21.9 kg  
 "Cold-start" function

### System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.