

3DP-PLA-01-MTW

Filament, matte PLA, white, 1.75 mm, 1 kg

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment
- The material is composed of PLA and ester
- Matte surface



- High precision roundness enables higher printing quality
- No bubbles, vivid colors

Features

- Can be applied to a variety of 3D printers

Specifications

Material: PLA, 1.75 mm diameter Weight: 1 kg/spool (2.2 lbs) Length: approx. 340 m Density at 21.5 °C: 1.21 g/cm3 Melt Flow Index at 10min, 2.16kg: 6...8

Melt Point: 190 220 °C

Heat-Deflection-Temperature at 0.455 MPa: 50 °C

Yield Strength at 5mm/min: > 30 MPa

Impact Strength: 5 KJ/m2 Tensile Break: 20 % Diameter: 1.75 ± 0.05 mm

Spool dimensions: 200 mm diameter x 67 mm height x 60 mm central hole

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code

8 0.033 11.06 75x215x215 mm 450x310x235 mm CN 8716309127127 3916909000

System requirements

A 3D printer with 1.75 mm extruder of temperature around 200 $^{\circ},$ suitable for PLA filament

Certificates





