

3DP-PLA-01-MTW

## Filament, matte PLA, white, 1.75 mm, 1 kg

### VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment
- The material is composed of PLA and ester
- Matte surface



### Funkcijos

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

### Packaging

Dėžių kiekis, vnt	8
Dėžių dydis, CUM	0.033
Dėžių svoris, kg	11.06
Individual package size LxWxH:	75x215x215 mm
Kilmės šalis	450x310x235 mm
Kilmės šalis	CN
Brūkšninis kodas	8716309127127
Customs code	3916909000

### Techniniai duomenys

Material: PLA, 1.75 mm diameter  
Weight: 1 kg/spool (2.2 lbs)  
Length: approx. 340 m  
Density at 21.5 °C: 1.21 g/cm<sup>3</sup>  
Melt Flow Index at 10min, 2.16kg: 6...8  
Melt Point: 190 220 °C  
Heat-Deflection-Temperature at 0.455 MPa: 50 °C  
Yield Strength at 5mm/min: > 30 MPa  
Impact Strength: 5 KJ/m<sup>2</sup>  
Tensile Break: 20 %  
Diameter: 1.75 ± 0.05 mm  
Spool dimensions: 200 mm diameter x 67 mm height x 60 mm central hole

### Sistemos reikalavimai

A 3D printer with 1.75 mm extruder of temperature around 200 °, suitable for PLA filament

### Sertifikatai

