

PDU, 0U rack, 16A, C13 EG-PDU-010

- ReMote beheer: Hiermee kun je toegang krijgen tot het configureren en beheren van de PDU vanaf externe locaties via SSL web (https) en SNMP-controle.



Kenmerken

- Remote Power Management (on/off)
- SNMP Control and SSL Web Browser (Https) for Setup and management
- Remote Total PDU Power Monitoring
- True RMS Current Metering & Reporting
- Alarm Threshold Sensing
- User Defined Alarm Thresholds
- Alarm Notification via Email, SNMP, Syslog, LED or Audible Alarm.
- User Defined Power On/OFF Sequence Time.
- Memorized Power-Up Previous Status

Verpakking

Verpakkinghoeveelheid/stuks	1
Volume doos/CUM	0.03
Gewicht doos/kg	5.86
Afmetingen productverpakking LxBxH:	1850x145x110 mm
Afmetingen transportverpakking LxBxH:	1850x145x110 mm
Land van herkomst	TW
Streepjescode	8716309067539
Douanecode	8537109120

Specificaties

RJ45:1pcs;10M Ethernet;ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, SNMPv1
Reset Hole:1pcs;Hardware Reset;
Button:1pcs;Function;1 beeps : Current, Temp./Humidity Display 2 Beeps : IP Display. 4 Beeps : DHCP/Fixed 6 Beeps : Reset to Default

Seven Segments:3 digits;Current True RMS Meter Range: 0A ~ 20 A
Resolution: 0.1A Precision: +/-2%/+/-0.1AMP
IP;Press Button after 2 Beeps will display PDU IP Address
Yellow LED:1pcs;ON: SSL is enabled
Green LED:1pcs;IP;ON: DHCP is enabled
Green LED:24pcs;Power Status
Output:24pcs;IEC320 C13 x 21 IEC320 C19 x 3

Certificaat/Certificaten

