



Bi-directional SATA/IDE converter

SATA-IDE-2

GET MORE OUT OF YOUR PC

- Converts SATA to IDE and IDE to SATA
- Extend the life of your IDE devices



Features

- Turns 'older' IDE devices into SATA devices
- Allows recent SATA devices to be connected to 'older' IDE host controllers
- Supports Serial ATA 1.0 interface with data transfer rates up to 150 MBytes/sec
- Supports all UDMA-33/66/100/133/150 IDE hard drives and most ATAPI devices
- Easy installation, no drivers required

Specifications

Native Hot-Swap and Plug & Play capability (non-boot device)

Standard female IDE 40-pin connector
 Standard 7-pin Serial ATA connector
 Chipset: JM20330
 Dimensions: 52 x 48 mm
 Net weight: 12 g

Packaging

Q'ty in crtn, pcs	40
Crtn volume, CUM	0.033728
Crtn weight, kgs	4.96
Individual package size LxWxH:	160x30x145 mm
Carton size LxWxH:	340x320x310 mm
Country of origin	CN
Barcode	8716309067805
Customs code	8522900090

System requirements

No drivers required under Windows 8/7/Vista/XP/2000/Me/NT/98SE/95/3.1 and DOS 5.0

Package contents

Bi-directional SATA-IDE converter card
 SATA cable, 0.3 m
 Power cable, 0.18 m

Certificates

