

Rack 1500VA UPS

UPS-RACK-1500

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Īpašības

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Skaitis iepakojumā, gab.	1
Iepakojuma izmērs, kub.m	0.04922
Iepakojuma svars, kg	15.9
Individual package size LxWxH:	535x400x230 mm
Carton size LxWxH:	535x400x230 mm
Izcelsmes valsts	CN
Svītrkods	8716309074797
Customs code	8504408490

Iepakojuma saturs

UPS
Power cord
USB cable
Software CD
Spare fuse

Specifikācija

UPS type: line interactive
 Input: 220V AC \pm 25%, 50Hz / 60Hz \pm 10%
 Output: 220V AC \pm 10%, 50Hz / 60Hz \pm 0.5% (on battery)
 Switching time: no more than 10 ms (typically 6 ms)
 Backup time: 8...20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 8 Ah / 2.3 kg x 2 pcs
 Charge time: up to 12 hours
 Sockets: IEC13 output x 4 pcs, input IEC14, USB-BF control interface, telephone input/output
 Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing
 Noise: < 45 dB (at 1 meter distance)

Sistēmas prasības

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Sertifikāti

