

EnerGenie Programmable surge protector with WLAN interface

EG-PMS2-WLAN

YOUR SWITCH IS MY COMMAND

- EG-PMS2-WLAN is an advanced surge protector with power management features. It is possible to individually switch 4 sockets on or off manually via your local WiFi network or Internet, by timer schedule, or by programmable special events (eg: switch on my scanner whenever I start Photoshop, or have my printer switched on only when I really print). With your free personal user account on EnerGenie.com you can manage your EG-PMS2-WLAN via Internet from all over the world, even with your smartphone.
- Stay in control of all your electrical devices at home or in the office
- Program four sockets individually via WLAN or Internet
- Switch electric devices on or off with your smartphone, wherever you are
- Protect your valuable equipment
- An advanced standby-killer for computer peripherals
- Perfect solution for security systems , sauna , aquariums, pet habitats, etc.



Características

- Switch individual sockets on/off manually from your computer
- Switch individual sockets on/off by a programmable timer schedule
- Switch individual sockets on/off whenever a certain software event occurs (e.g. Windows/other software start-up/shutdown, print spooler starting and finishing its job, etc)
- Because of the WLAN interface and the built-in web-server, EG-PMS2-WLAN can be accessed from any computer within your wireless local network (via an Internet browser or Power manager software)

Embalaje

Qtd por caja, pcs	10
Volumen caja, M3	0.04545375
Peso caja, kgs	12.47
Medidas cajas individuales LxWxH:	400x140x60 mm
Medidas caja LxWxH	425x345x310 mm
Pais de origen	CN
Código de barras	8716309076784
codigo de aduanas	8536301090

Contenido de la caja

EG-PMS2-WLAN
 USB cable
 WLAN antenna
 User manual and Quick installation guide
 CD with Power Manager software for Windows

Especificaciones

Input voltage: up to 250 VAC, 50 – 60 Hz
 Maximum load current: 10 A
 Maximum power consumption: 3.5 W
 Surge protection: Type3, Up=1.2KV for L-N, Uoc=4KV for L-N
 Uo=230V Uc=250V Ucs=1.1X230V=253V
 Built-in power supply
 Wireless LAN: IEEE 802.11 b/g
 Hardware schedule possibilities:
 Maximum number of independent hardware schedule events – 45 per socket
 Time setting accuracy in seconds
 Combine periodical and once events

Requisitos del sistema

Local area network with a WLAN switch/router
 For the initial setup and Power Manager software: Windows® 2000/XP/Vista or Windows 7/8 computer
 Any Internet-enabled or WiFi-enabled computer or PDA and any Internet-browser software

Certificados

