

Server power supply unit (1U), 250 W

CCC-PSU-1U-001

- Pure power for your server



Īpašības

- 1U power supply unit for servers
- Active PFC
- Fully protected: over voltage protection, short-circuit protection, fan speed thermal Control
- Suitable for use with 19CC-1U-001 1U rack mount chassis

Packaging

Skaitis iepakojumā, gab.
Iepakojuma izmērs, kub.m
Iepakojuma svars, kg
Individual package size LxWxH:
Carton size LxWxH:
Izcelsmes valsts
Svītrkods
Customs code

12
0.02
9.92
220x85x45 mm
510x360x110 mm
CN
8716309079303
8536301090

Specifikācija

MTBF: 100,000 hours
Motherboard support: FLEX-ATX / TFX12V
Input voltage: 115 230 V AC
Input current: 4A at 115 VAC; 2A at 230 VAC
Voltage frequency: 47 ~ 63 Hz
Hold up time: 16 ms at full load
Over voltage protection: +5 V Output, 7V Max; +3.3V Output, 4.3V Max; +12V Output, 15.6V Max
Dimensions (L x W x H): 150 x 81.5 x 40.3 mm
Operating / storage temperature: 0 ~ 40 / -20 ~ 60 Celsius degrees, 5 ~ 95% RH
Connectors: 24 pin, 4 pin, SATA x 2 pcs, MOLEX x 1 pc, Floppy x 1 pcs

Sertifikāti

