

UPS with LCD display, 650 VA, black

EG-UPS-031

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Jellemzők

- Uninterruptable 650 VA power supply with modified sine wave output
- Automatic AC voltage regulation (AVR)
- Intelligent surge-, overload and short-circuit protection
- Audible and visual alarms
- LCD status display
- Intelligent battery management with overcharge and over-discharge protection

Packaging

| | |
|--------------------------------|----------------|
| Darab / karton | 3 |
| Csomag térfogata, m3 | 0.04158 |
| Karton súlya, kg | 17.08 |
| Individual package size LxWxH: | 375x150x230 mm |
| Carton size LxWxH: | 450x385x240 mm |
| Származási hely | CN |
| Vonalkód | 8716309080835 |
| Customs code | 8504408490 |

Csomag tartalom

UPS
Power cord
Spare fuses
User manual

Részletes leírás

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)
Input: 220 V AC \pm 25%, 50 / 60 Hz \pm 10%
Output: 220 V AC \pm 10%, 50 / 60 Hz \pm 1% (220 V AC \pm 5 % at inverter mode)
Switching time about or less than 8 ms
Backup time: 8...20 mins (depends on the load)
Battery: sealed lead-acid 12 V DC / 7Ah
Charge time: up to 12 hours
Output sockets: 2 pcs x C13, 1 pc x german Shuko
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Rendszerkövetelmények

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Tanúsítványok

