

# UPS with LCD display, 650 VA, black

EG-UPS-031

## ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



## Īpašības

- Uninterruptable 650 VA power supply with modified sine wave output
- Automatic AC voltage regulation (AVR)
- Intelligent surge-, overload and short-circuit protection
- Audible and visual alarms
- LCD status display
- Intelligent battery management with overcharge and over-discharge protection

## Packaging

Skaitis iepakojumā, gab.	3
Iepakojuma izmērs, kub.m	0.04158
Iepakojuma svars, kg	17.08
Individual package size LxWxH:	375x150x230 mm
Carton size LxWxH:	450x385x240 mm
Izcelsmes valsts	CN
Svītrkods	8716309080835
Customs code	8504408590

## Iepakojuma saturs

UPS  
Power cord  
Spare fuses  
User manual

## Sertifikāti



## Specifikācija

Type: line interactive  
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC  $\pm$  25%, 50 / 60 Hz  $\pm$  10%  
Output: 220 V AC  $\pm$  10%, 50 / 60 Hz  $\pm$  1% (220 V AC  $\pm$  5 % at inverter mode)

Switching time about or less than 8 ms  
Backup time: 8...20 mins (depends on the load)  
Battery: sealed lead-acid 12 V DC / 7Ah  
Charge time: up to 12 hours  
Output sockets: 2 pcs x C13, 1 pc x german Shuko  
Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 650 VA (390 W)  
Charging current: up to 1.2 A  
Noise: < 45 dB at 1 m distance  
Dimensions: 340 x 95 x 165 mm  
Product weight: 5.2 kg  
"Cold-start" function

## Sistēmas prasības

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.