

UPS with USB and LCD display, 1200 VA, black

EG-UPS-033

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Karakteristike

- Uninterruptable 1200 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

Pakovanje i slike

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.04575
Crtn weight, kgs	26.38
Individual package size LxWxH:	450x180x295 mm
Carton size LxWxH:	375x400x305 mm
Country of origin	CN
Barcode	8716309080873
Customs code	8504408590

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Sertifikati



Specifikacije

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC \pm 25%, 50 / 60 Hz \pm 10%

Output: 220 V AC \pm 10%, 50 / 60 Hz \pm 1% (220 V AC \pm 5 % at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7 Ah x 2 pcs (connected in series)

Charge time: up to 12 hours

Output sockets: 3 pcs x C13, 2 pcs x german Shuko

USB control interface: BF socket

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 1200 VA (720 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 400 x 125 x 220 mm

Net weight: 10.4 kg

"Cold-start" function

Sistemski zahtevi

Software is compatible with Windows Vista, Windows 7/8/10/11, Windows 2008 server