

Premium high efficiency LED lamp, 8 W, E27 socket, 2700 K

EG-LED0827-01



- Revolutionary thermal design
- Improved light radiation angle up to 330°
- Ultra light weight design
- Super energy efficient up to 135 lumens per watt
- Guaranteed longer lifetime
- Best quality light!
- EnerGenie LED bulb — the world’s best! We used a unique 3D placement of the LED’s in our EnerGenie LED bulb as opposed to the traditional flat surface 2D placement of LED’s in most other bulbs. This results in a far better light distribution area of 330°, while most other LED bulbs barely provide 140°–160° light angles. The EnerGenie LED bulb produces an awesome 135 lumens per watt. This is around 40 % better than the traditional LED bulbs!
- Guaranteed longer lifetime!
- In addition to 2 year warranty: 3 years of free repair service, if required

Features

- 8 W high efficiency LED bulb, 1080 lm
- True replacement for 70 W incandescent light bulb
- Innovative heat-pipe cooling technology for a longer lifetime
- Very low energy consumption, saving at least 88% energy
- High color rendering (CRI 85) for vivid colors
- No warm-up time, instant 100% light
- E27 cap can be easily fitted to replace ordinary light bulbs
- Long service life of 50.000 hours

Packaging

Q'ty in crtn, pcs	40
Crtn volume, CUM	0.028
Crtn weight, kgs	4.2
Individual package size LxWxH:	60x60x135 mm
Carton size LxWxH:	500x335x165 mm
Country of origin	CN
Barcode	8716309082907
Customs code	8543709099

Certificates



Specifications

Power consumption: 8 W (up to 110 mA)
 CRI: > 80 (84 86)
 Luminous flux: up to 1080 lm
 CCT (correlated color temperature): 2700 °K (warm white)
 Lifetime span: ca. 50.000 Hours
 Input voltage: 85-260 V AC at 50 60 Hz
 Power factor: 0.876
 Energy Efficiency Class: A
 Radiation angle: 330 °
 Switching cycles: at least 300.000
 Net weight: 80 g
 Dimensions: O50 x 120 mm
 Operating temperature: -20 ... 40 °C
 Dimmable: no
 Shadow in luminary: almost zero
 UV and NIV radiation: free
 LEDs: 28 pcs

System requirements

Light fixture with E27 socket