

## Rack UPS, 2000 VA, black

EG-UPSRACK-12

### ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



### Īpašības

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

### Packaging

Skaitis iepakojumā, gab.  
Iepakojuma izmērs, kub.m  
Iepakojuma svars, kg  
Individual package size LxWxH:  
Carton size LxWxH:  
Izcelsmes valsts  
Svītrkods  
Customs code

1  
0.076632  
25.06  
525x400x225 mm  
620x515x240 mm  
CN  
8716309087735  
8504408590

### Iepakojuma saturs

UPS  
Power cord  
USB cable  
Software CD  
Spare fuse

### Sertifikāti



### Specifikācija

UPS type: line interactive, pure sine wave  
Input: 220V AC  $\pm$  25%, 50Hz / 60Hz  $\pm$  10%  
Output: 220V AC  $\pm$  10%, 50Hz / 60Hz  $\pm$  0.5% (on battery)  
Output power factor: 0.8  
Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: no more than 10 ms (typically 6 ms)  
Backup time: 8...20 mins (depends on the load)  
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs

Charge time: up to 12 hours  
Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)  
Power: 2000 VA (1600 W)  
Dimensions: 440 x 410 x 132 mm  
Product weight: 19.8 kg  
"Cold-start" function

### Sistēmas prasības

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.