

FF-3DP-2ND-01

Flashforge Dreamer 3D Printer

FRIENDLY & EASY TO USE

- Equipped with many versatile features, the Dreamer enables you to create practical & interesting objects for all your home, business or educational needs.
- Modular design dual extruder more possibilities, easier replacement
- Versatile, closable printing chamber
- Includes easy to use FlashPrint Slicing Software



Features

- FDM 3D printer with dual nozzle for use with ABS/PLA/PVA filament
- 3.5-inch touch screen panel
- Print preview function (gx format)
- 16-language package for multilingual operation
- Strong 6.5 mm non-deforming alloy printing platform (heated)
- Patented dual extruder structure which is compatible with different filament types
- Fully-closed design with automatic temperature control
- Connectivity: WIFI, SD card, USB cable
- Powered by Flashprint easy to use slice software

Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.124656
Crtn weight, kgs	16.6
Individual package size LxWxH:	565x535x430 mm
Carton size LxWxH:	560x420x530 mm
Country of origin	CN
Barcode	8716309088299
Customs code	8477809990

Package contents

- 3D printer
- PLA Filament, 0.6 kg
- ABS Filament, 0.6 kg
- Build tape
- SD Card
- Power cord
- Leveling tool
- Tool box
- Scraper
- Tweezer
- Scrapers
- Graver

Certificates



Specifications

Principle: FDM
 Build size: up to 230 x 150 x 140 mm
 Filament: ABS/PLA/PVA spool, 1.75mm
 Print precision: ±0.10mm
 Positioning precision: Z axis 0.0025 mm, XY axis 0.011 mm
 Layer thickness: 0.1 0.5 mm
 Nozzle diameter: 0.40 mm
 Extruder temperature: 220 °C
 Power consumption: 100 240V AC, up to 300 W
 Slicing software: Flashprint
 Heating plate temperature: ABS: 110 115 °C / PLA: 50 °C
 File type Input: STL/OBJ, Output X3G
 Weight: NW 15 kg, GW 23 kg
 Dimensions: 480 x 400 x 335mm

System requirements

Windows XP/Vista/7/8/10
 Connection: USB cable or SD-card