



Filament, PLA Black, 1.75 mm, 1 kg

3DP-PLA1.75-01-BK

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Features

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Q'ty in crtn, pcs	8
Crtn volume, CUM	0.036
Crtn weight, kgs	11.56
Individual package size LxWxH:	210x210x85 mm
Carton size LxWxH:	440x440x185 mm
Country of origin	CN
Barcode	8716309088367
Customs code	3916909000

Specifications

Material: PLA, 1.75 mm diameter
 Weight: 1 kg/spool (2.2 lbs)
 Length: approx. 330 m
 Density at 21.5 °C: 1.25 g/cm3
 Melt Flow Index at 10min, 2.16kg: 5
 Melt Point: 190 220 °C
 Heat-Deflection-Temperature at 0.455 MPa: 50 °C
 Yield Strength at 5mm/min: 45 MPa
 Impact Strength: 5 KJ/m2
 Ensile Break: 20 %
 Diameter: 1.75 ± 0.05 mm

System requirements

A 3D printer with 1.75 mm extruder of temperature around 200 °, suitable for PLA filament

Certificates

