

3DP-PLA1.75-01-R

Filament, PLA Red, 1.75 mm, 1 kg

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment.



Funkcijos

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Dėžių kiekis, vnt	8
Dėžių dydis, CUM	0.036
Dėžių svoris, kg	11.47
Individual package size LxWxH:	210x210x85 mm
Kilmės šalis	440x440x185 mm
Kilmės šalis	CN
Brūkšninis kodas	8716309088572
Customs code	3916909000

Techniniai duomenys

Material: PLA, 1.75 mm diameter
Weight: 1 kg/spool (2.2 lbs)
Length: approx. 330 m
Density at 21.5°C: 1.25 g/cm³
Melt Flow Index at 10min, 2.16 kg: 5
Melt Point: 190 220 °C
Heat-Deflection-Temperature at 0.455 MPa: 50 °C
Yield Strength at 5mm/min: 45 MPa
Impact Strength: 5 KJ/m²
Ensil Break: 20 %
Diameter: 1.75 ± 0.05 mm
Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole

Sistemos reikalavimai

A 3D printer with 1.75 mm extruder of temperature around 200 °, suitable for PLA filament

Sertifikatai

