




### **ABS Filament Lime, 3 mm, 1 kg**

3DP-ABS3-01-LM

#### **VERSATILE & EASY TO USE**

- Acrylonitrile butadiene styrene (ABS) is a common thermoplastic strong, flexible durable plastic available in a range of colors.
- ABS is the plastic used in lots of things around us and is perfect for heated plastic extrusion 3D printing.



#### **Features**

- High strength, good toughness
- Low density: when printing larger volume the model is lighter
- Can be applied to a variety of 3D printers

#### **Packaging**

Q'ty in crtn, pcs	12
Crtn volume, CUM	0.051
Crtn weight, kgs	15.5
Individual package size LxWxH:	180x180x120 mm
Carton size LxWxH:	380x355x380 mm
Country of origin	CN
Barcode	8716309088886
Customs code	3916909000

#### **Specifications**

Material: ABS, 3 mm diameter  
 Weight: 1 kg/spool (2.2 lbs)  
 Length: approx. 140 m  
 Density at 21.5°C: 1.01 g/cm<sup>3</sup>  
 Melt Flow Index at 10min, 2.16kg: 5  
 Melt Point: 225-240 °C  
 Heat-Deflection-Temperature at 0.455 MPa: 85 °C  
 Yield Strength at 5mm/min: 45 MPa  
 Impact Strength: 16 KJ/m<sup>2</sup>  
 Elongation at Break: 30 %  
 Diameter: 3.00 ± 0.05 mm

#### **System requirements**

A 3D printer with 3 mm extruder of temperature around 230 °C, suitable for use with ABS filament

#### **Certificates**

