



### **PLA Gold, 3 mm, 1 kg**

3DP-PLA3-01-GL

#### **VERSATILE & EASY TO USE**

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



#### **Características**

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

#### **Embalaje**

Qtd por caja, pcs	12
Volumen caja, M3	0.052
Peso caja, kgs	15.4
Medidas cajas individuales LxWxH:	180x180x110 mm
Medidas caja LxWxH	380x360x380 mm
Pais de origen	CN
Código de barras	8716309089098
codigo de aduanas	3916909000

#### **Especificaciones**

Material: PLA, 3 mm diameter  
 Weight: 1 kg/spool (2.2 lbs)  
 Length: approx. 120 m  
 Density at 21.5°C: 1.25 g/cm<sup>3</sup>  
 Melt Flow Index at 10min, 2.16kg: 5  
 Melt Point: 190 220 °C  
 Heat-Deflection-Temperature at 0.455 MPa: 50 °C  
 Yield Strength at 5mm/min: 45 MPa  
 Impact Strength: 5 KJ/m<sup>2</sup>  
 Ensile Break: 20 %  
 Diameter: 3.00 ± 0.05 mm

#### **Requisitos del sistema**

A 3D printer with 3 mm extruder of temperature around 200 °C, suitable for PLA filament

#### **Certificados**

