

3DP-HIPS1.75-01-R

Filament, HIPS Red, 1.75 mm, 1 kg

VERSATILE & EASY TO USE

- Practical liquid soluble HIPS material (High impact polystyrene) is a versatile, economical and impact-resistant support material.
- HIPS is soluble in Limonene and can be glued by acetone or superglue (Cyanoacrylate).
- Can be used as both standalone material and support material for over-lengths and holes in ABS parts.



Características

- HIPS filament
- Maintains strength in high-impact applications
- Easily moldable, good dimensional stability and low volatility
- Suitable for use in a variety of 3D printers
- Can be easily glued and painted

Embalaje

Cantidad por caja, pcs	8
Volumen caja, M3	0.036
Peso caja, kgs	11.14
Medidas cajas individuales LxWxH:	210x210x85 mm
Medidas caja LxWxH	440x440x185 mm
País de origen	CN
Código de barras	8716309089180
codigo de aduanas	3916909000

Especificaciones

Material: HIPS, 1.75 mm diameter
Weight: 1 kg/spool (2.2 lbs)
Length: approx. 400 m
Density at 21.5°C: 1.04 g/cm³
Melt Flow Index at 10min, 2.16kg: 4
Melt Point: 225 240 °C
Heat-Deflection-Temperature at 0.455 MPa: 7 °C
Yield Strength at 5mm/min: 80 90 MPa
Impact Strength: 10 KJ/m²
Ensil Break: 55 %
Diameter: 1.75 ± 0.05 mm
Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole

Requisitos del sistema

A 3D printer with 1.75 mm extruder of temperature around 230 °C, suitable for HIPS filament
Do not remove 3D printed parts until they are fully cooled down

Certificados

