



HIPS Tan, 3 mm, 1 kg

3DP-HIPS3-01-TN

VERSATILE & EASY TO USE

- Practical liquid soluble HIPS material (High impact polystyrene) is a versatile, economical and impact-resistant support material.
- HIPS is soluble in Limonene and can be glued by acetone or superglue (Cyanoacrylate).
- Can be used as both standalone material and support material for over-lengths and holes in ABS parts.



Features

- HIPS filament
- Maintains strength in high-impact applications
- Easily moldable, good dimensional stability and low volatility
- Suitable for use in a variety of 3D printers
- Can be easily glued and painted

Packaging

Q'ty in crtn, pcs	12
Crtn volume, CUM	0.049
Crtn weight, kgs	16
Individual package size LxWxH:	180x180x110 mm
Carton size LxWxH:	375x350x375 mm
Country of origin	CN
Barcode	8716309089548
Customs code	3916909000

Specifications

Material: HIPS, 3 mm diameter
 Weight: 1 kg/spool (2.2 lbs)
 Length: approx. 140 m
 Density at 21.5°C: 1.04 g/cm³
 Melt Flow Index at 10min, 2.16kg: 4
 Melt Point: 225 240 °C
 Heat-Deflection-Temperature at 0.455 MPa: 7 °C
 Yield Strength at 5mm/min: 80 90 MPa
 Impact Strength: 10 KJ/m²
 Ensile Break: 55 %
 Diameter: 3.00 ± 0.05 mm

System requirements

A 3D printer with 3 mm extruder of temperature around 230 °C, suitable for HIPS filament
 Do not remove 3D printed parts until they are fully cooled down

Certificates

