



### **ABS Red, 1.75 mm, 0.6 kg**

FF-3DP-ABS1.75-02-R

#### **VERSATILE & EASY TO USE**

- Acrylonitrile butadiene styrene (ABS) is a common thermoplastic strong and durable plastic available in a range of colors.
- ABS is the plastic used in lots of things around us and is perfect for heated plastic extrusion 3D printing.



#### **Features**

- ABS filament with 1.75 mm diameter
- Excellent chemical resistance
- High Stiffness and good impact resistance at low temperatures
- Easily processed with good surface finish
- Can be used in a variety of 3D printers
- 0.6 kg spool

#### **Packaging**

Q'ty in crtn, pcs	12
Crtn volume, CUM	0.03
Crtn weight, kgs	10.28
Individual package size LxWxH:	210x210x90 mm
Carton size LxWxH:	360x360x230 mm
Country of origin	CN
Barcode	8716309091602
Customs code	3916909000

#### **Specifications**

Material: ABS, 1.75 mm diameter  
 Weight: 0.6 kg/spool  
 Density at 215°C: 1.05 g/cm3  
 Melt Flow Index at g/10min, 220°C/ 5kg: 1.8  
 Melt Point: 210 250 °C  
 Heat-Deflection-Temperature at 0.455 MPa: 85 100 °C  
 Yield Strength at 5mm/min: 45 MPa  
 Impact Strength: 18 KJ/m2  
 Ensile Break: 25 %  
 Diameter: 1.75 ± 0.05 mm

#### **System requirements**

A 3D printer with 1.75 mm extruder of temperature around 230 °C, suitable for ABS filament

#### **Certificates**

