

FF-3DP-PLA1.75-02-G

Flashforge Filament Green, 1.75 mm, 600 gram

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Funkcijos

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Dėžių kiekis, vnt	20
Dėžių dydis, CUM	0.059
Dėžių svoris, kg	19.4
Individual package size LxWxH:	195x195x65 mm
Kilmės šalis	410x340x420 mm
Kilmės šalis	CN
Brūkšninis kodas	8716309091794
Customs code	3916909000

Techniniai duomenys

Material: PLA, 1.75 mm diameter
Weight: 0.6 kg/spool
Density at 215°C: 1.24 g/cm³
Melt Flow Index at g/10min, 190°C/ 2.16kg: 6
Melt Point: 190 220 °C
Heat-Deflection-Temperature at 0.455 MPa: 50 °C
Yield Strength at 5mm/min: 62 MPa
Impact Strength: 4.2 KJ/m²
Elongation at Break: 15 %
Diameter: 1.75 ± 0.05 mm

Sistemos reikalavimai

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Sertifikatai

