



Flashforge Filament Green, 1.75 mm, 600 gram

FF-3DP-PLA1.75-02-G

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Χαρακτηριστικά

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Συσκευασία

Ποσότητα ανά χαρτοκιβώτιο, τμχ	20
Όγκος χαρτοκιβωτίου, CUM	0.059
Βάρος χαρτοκιβωτίου, Kg	19.4
Μέγεθος ατομικής συσκευασίας LxWxH:	195x195x65 mm
Διαστάσεις χαρτοκιβωτίου LxWxH:	410x340x420 mm
Χώρα προέλευσης	CN
Barcode	8716309091794
Τελωνειακός κώδικας	3916909000

Προδιαγραφές

Material: PLA, 1.75 mm diameter
 Weight: 0.6 kg/spool
 Density at 215°C: 1.24 g/cm³
 Melt Flow Index at g/10min, 190°C/ 2.16kg: 6
 Melt Point: 190 220 °C
 Heat-Deflection-Temperature at 0.455 MPa: 50 °C
 Yield Strength at 5mm/min: 62 MPa
 Impact Strength: 4.2 KJ/m²
 Ensile Break: 15 %
 Diameter: 1.75 ± 0.05 mm

Απαιτήσεις συστήματος

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Πιστοποιητικά

