



Flashforge PLA White, 1.75 mm, 0.6 kg

FF-3DP-PLA1.75-02-W

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Características

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers
- 0.6 kg spool

Embalaje

Qtd por caja, pcs	20
Volumen caja, M3	0.054
Peso caja, kgs	19.35
Medidas cajas individuales LxWxH:	195x195x60 mm
Medidas caja LxWxH	400x325x415 mm
Pais de origen	CN
Código de barras	8716309091855
codigo de aduanas	3916909000

Especificaciones

Material: PLA, 1.75 mm diameter
 Weight: 0.6 kg/spool
 Density at 215°C: 1.24 g/cm3
 Melt Flow Index at g/10min, 190°C/ 2.16kg: 6
 Melt Point: 190 220 °C
 Heat-Deflection-Temperature at 0.455 MPa: 50 °C
 Yield Strength at 5mm/min: 62 MPa
 Impact Strength: 4.2 KJ/m2
 Ensile Break: 15 %
 Diameter: 1.75 ± 0.05 mm

Requisitos del sistema

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Certificados

