



Flashforge PLA Transparent, 1.75 mm, 0.6 kg

FF-3DP-PLA1.75-02-TR

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment.



Eigenschaften

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers
- 0.6 kg spool

Verpackungsdetails

Stückzahl pro Karton	20
Karton Volumen, m ³	0.058
Kartongewicht, kg	19.33
Abmessungen Verpackung (LxBxH):	195x190x60 mm
Abmessungen Umkarton (LxBxH):	405x340x420 mm
Ursprungsland	CN
EAN Code	8716309094337
Zolltarif-Nr.:	3916909000

Spezifikationen

Material: PLA, 1.75 mm diameter
 Weight: 0.6 kg/spool
 Density at 215°C: 1.24 g/cm³
 Melt Flow Index at g/10min, 190°C/ 2.16kg: 6
 Melt Point: 190 220 °C
 Heat-Deflection-Temperature at 0.455 MPa: 50 °C
 Yield Strength at 5mm/min: 62 MPa
 Impact Strength: 4.2 KJ/m²
 Ensile Break: 15 %
 Diameter: 1.75 ± 0.05 mm

Systemvoraussetzungen

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

CE-Erklärung

