

FF-3DP-PLA1.75-02-TR

Flashforge PLA Transparent, 1.75 mm, 0.6 kg

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Cechy produktu

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers
- 0.6 kg spool

Opakowanie

Ilość sztuk w kartonie	20
Objętość kartonu	0.058
Waga kartonu, kg	19.33
Wymiary opakowania:	195x190x60 mm
Wymiary kartonu DxSxW	405x340x420 mm
Kraj pochodzenia	CN
Kod kreskowy EAN	8716309094337
Kod celný	3916909000

Specyfikacja

Material: PLA, 1.75 mm diameter
Weight: 0.6 kg/spool
Density at 215°C: 1.24 g/cm³
Melt Flow Index at g/10min, 190°C/ 2.16kg: 6
Melt Point: 190 220 °C
Heat-Deflection-Temperature at 0.455 MPa: 50 °C
Yield Strength at 5mm/min: 62 MPa
Impact Strength: 4.2 KJ/m²
Elongation at Break: 15 %
Diameter: 1.75 ± 0.05 mm

Wymagania systemowe

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Certyfikaty

