

size: 200x45x145 mm

877C

M: 100
Y: 100
K: 100

K: 80
K: 30
326C



USB TO SATA INTERFACE ADAPTER



- ▶ COMPATIBLE WITH ANY SERIAL ATA HARD DRIVE
- ▶ SMART REMOVABLE STORAGE SOLUTION
- ▶ WINDOWS® 7 COMPATIBLE

GIGABYTES IN YOUR POCKET



USB TO SATA INTERFACE ADAPTER



AUS01
PART NUMBER



GEMBIRD EUROPE B.V.
WWW.GEMBIRD.EU

SHAPING THE PERFECTION



- ### SYSTEM REQUIREMENTS
- Windows® 2000/XP, Vista, Windows® 7, MAC OS v.9.1 or above
 - 133 MHz CPU or better
 - USB 2.0 port (USB 1.1 supported, with lower speed)

- ### SPECIFICATION
- Supports USB 2.0 and USB 1.1 interfaces
 - Supports Serial ATA II specification 1.0
 - Supports USB mass storage device driver of the operating system
 - ESD protection up to 2000 V
 - Supports LBA48 bit addressed drives
 - AC-DC adapter: 100 V - 240 V AC 47-63 Hz input, 12 V DC/2 A and 5 V DC/2 A output, VDE and UL certified

- ### PACKAGE CONTENTS
- USB-SATA adapter
 - AC-DC power adapter with power cord
 - IDE-SATA power cable
 - Driver CD for Windows® 98SE
 - User manual

- ### CARATTERISTICHE
- Supporta ogni supporto di interfaccia SATA, incluso LBA indirizzato a 48 bit
 - Adattatore di potenza incluso
 - Velocità reale fino a 30 MB/sec.
 - Limitata solo dall'interfaccia USB 2.0 e dalle possibilità del proprio supporto

- ### ХАРАКТЕРИСТИКИ
- Поддерживаются любые накопители с SATA интерфейсом, включая носители с LBA48-битной адресацией
 - Блок питания для накопителя – в комплекте
 - Реальная скорость до 30 МБ/сек - ограничена только интерфейсом USB 2.0 и возможностями накопителя

- ### EIGENSCHAFTEN
- Ondersteunt elke SATA interface drive, inclusief LBA48 bit geaddressseerd
 - Power adapter voor uw drive is bijgevoegd
 - Real speed tot 30 MB/sec, alleen gelimiteerd door de USB 2.0 interface en uw drive capaciteit

- ### KENMERKEN
- Supports any SATA interface drives, including LBA48 bit addressed Power adapter for your drive is enclosed
 - Real speed up to 30 MB/sec, limited only by the USB 2.0 interface and your drive capability

- ### FEATURES
- Supports any SATA interface drives, including LBA48 bit addressed Power adapter for your drive is enclosed
 - Real speed up to 30 MB/sec, limited only by the USB 2.0 interface and your drive capability