



UPS with USB and LCD display



UPS with USB and LCD display



- Informative LCD display
- Provides backup power - prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable - ideal for home and small office use



850 VA



UPS with USB and LCD display

- Specifications:
- Type: line interactive
- Waveform: sine wave (AC main), modified (square) sine wave (battery)
- Input: 220V AC ± 25%, 50 Hz / 60 Hz ± 10%
- Output: 220V AC ± 10%, 50 Hz / 60 Hz ± 1% (220V AC ± 5% at inverter mode)
- Switching time: less than 10 ms
- Backup time: 8 - 20 mins (depends on the load)
- Battery: sealed lead acid 12V DC / 8 Ah
- Charge time: up to 12 hours
- Output sockets: 2 pcs x C13, 1 pcs x german Shuko
- USB control interface: RS-485
- Operating conditions: 0°C - 40°C, at humidity 20% - 90% RH non condensing
- Power: 850 VA (510 W)
- Charging current: up to 1.2 A
- Noise: < 45 dB at 1 m distance
- Dimensions: 340 mm x 95 mm x 165 mm
- Product weight: 7 kg

System requirements:

- Software is compatible with Windows® Vista, Windows® 7/8, Windows® 2008 server

- Package contents:
- UPS
- Power cord
- USB cable
- Software CD
- Spare fuse



EG-UPS-002



6 716399 080842



All brands and logos are registered trademarks of their respective owners.



- Informative LCD display
- Provides backup power - prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable - ideal for home and small office use



850 VA



UPS with USB and LCD display

- Unterbrechungsfreie 850 VA Power Supply for PCs
- Automatic output voltage regulation (AVR)
- USB interface
- LCD status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection
- Including practical UPS Management software

850 VA UPS met LCD, toekomstbestendig

- Automatische Ausgangsspannungsregulierung (AVR)
- USB-Schnittstelle
- LCD-Statusanzeige
- Kurzschlussicherung
- Überspannungs- und Sperrspannungsüberwachung sowie Blitzschutz
- Hörbare und sichtbare Alarme
- Absicherung vor Überladung und Tiefentladung

Источники бесперебойного питания 850 Вольт-ампер с ЖК-дисплеем и USB-интерфейсом

- Автоматический регулятор выходного напряжения (AVR)
- USB-интерфейс для управления и индикации
- ЖК-индикатор статуса
- Защита от коротких замыканий
- Защита от выбросов напряжения, помех и скачков
- Звуковые и визуальные оповещения о состоянии
- Защита батарей от перезарядки и глубокого разряда

Джерело безперебійного живлення 850 Вольт-ампер з ЖК-дисплеєм та USB-інтерфейсом

- Автоматичний регулятор вихідного напруги (AVR)
- USB-інтерфейс для управління і індикації
- ЖК-індикатор статусу
- Захист від коротких замикань
- Захист від викидів напруги, пошкодження та скачки
- Звукові і візуальні оповіщення про стан
- Захист батарей від перезарядки і глибокого розряду

UPS με οθόνη LCD και USB, 850 VA ισχύος

- Αυτόματη αλγόριθμος παρατήρησης ισχύος 850 VA για ηλεκτρονική ολοκλήρωση
- Αυτόματη ρύθμιση της τάσης (AVR)
- Διασύνδεση USB
- Οθόνη κατάστασης LCD
- Προστασία από βραχυκύκλωση
- Προστασία από αιχμηρές αυξήσεις τάσης, ηλεκτρονική
- Με ειδικούς και οπτικούς παύση/αποστολή
- Προστασία μπαταρίας και υπερφόρτισης
- Διατήρηση/αποφυγή πρακτική λειτουργία

size: 375x145x230 mm



Pantone blue 072C



Pantone 376C



60% black