




## 650 VA UPS

**Provides backup power**  
Prevents data loss

**Protects your sensitive and valuable equipment**

**Compact and reliable**  
Ideal for home and small office use



# BASIC



www.energenie.com


**Specifications:**


UPS type:	Line interactive
Input:	AC 220V ± 25%, 50 / 60 Hz ± 10%
Output:	AC 220V ± 10%, 50 / 60 Hz ± 0.5% (on battery)
Switching time:	no more than 10 ms
Backup time:	up to 20 mins (depends on the load)
Battery:	151 mm x 65 mm x 95 mm, sealed lead-acid 12 V / 7.7 Ah x 1 pcs
Charge time:	up to 12 hours
Sockets:	2 x Schuko output (CEE 7/4)
Operating conditions:	0°C – 40°C, at humidity 10 – 90% RH non condensing
Power:	650 VA (390 W)
Dimensions:	100 mm x 280 mm x 140 mm
Product weight:	4.3 kg


**Package contents:**



UPS  
User manual


All brands and logos are registered trademarks of their respective owners.








## 650 VA UPS

**Provides backup power**  
Prevents data loss

**Protects your sensitive and valuable equipment**

**Compact and reliable**  
Ideal for home and small office use



# BASIC



www.energenie.com

**Specifications:**




UPS type:	Line interactive
Input:	AC 220V ± 25%, 50 / 60 Hz ± 10%
Output:	AC 220V ± 10%, 50 / 60 Hz ± 0.5% (on battery)
Switching time:	no more than 10 ms
Backup time:	up to 20 mins (depends on the load)
Battery:	151 mm x 65 mm x 95 mm, sealed lead-acid 12 V / 7.7 Ah x 1 pcs
Charge time:	up to 12 hours
Sockets:	2 x Schuko output (CEE 7/4)
Operating conditions:	0°C – 40°C, at humidity 10 – 90% RH non condensing
Power:	650 VA (390 W)
Dimensions:	100 mm x 280 mm x 140 mm
Product weight:	4.3 kg



**Package contents:**


UPS  
User manual

All brands and logos are registered trademarks of their respective owners.





www.energenie.com

**650 VA UPS**

- Uninterruptible 650 VA power supply for PCs
- Automatic output voltage regulation (AVR)
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

**650 VA UPS mit AVR**

- Automatische Ausgangsspannungsregulierung (AVR)
- LED-Statusanzeige
- Kurzschlussicherung
- Überspannungs- und Spannungsspitzenabsicherung sowie Blitzschutz
- Hörbare und sichtbare Alarme
- Absicherung vor Überladung und Tiefentladung

**Noodstroomvoeding met AVR, 650 VA**

- 650 VA noodstroomvoeding (UPS) voor o.a. PC's
- Automatische AC-spanningsregelaar (AVR)
- Ingebouwde overspanningsbeveiliging biedt bescherming tegen kortsluiting en spanningspieken veroorzaakt door bijvoorbeeld blikseminslag
- Beveiligde fax/modem/telefoonaansluiting
- Hoörbaar en zichtbaar alarm bij stroomuitval
- LED status indicator
- Interne batterij met bescherming tegen overladen of teveel ontladen

**Источник бесперебойного питания 650 Вольт-ампер**

- Автоматический регулятор выходного напряжения (AVR)
- Светодиодная индикация статуса
- Защита от коротких замыканий
- Защита от выбросов напряжения, помех и молний
- Звуковые и визуальное оповещение о событиях
- Защита батареи от перезаряда и глубокого разряда




**Джерело безперебійного живлення 650 Вольт-ампер**

- 650 VA джерело безперебійного живлення 650 Вольт-ампер
- Автоматичний регулятор вихідної напруги (AVR)
- Світлодіодна індикація статусу
- Захист від короткого замикання
- Захист від викидає напруги, перепадів і блискавок
- Звукове і візуальне сповіщення про події
- Захист батареї від перезаряду і глибокого розряду

**650 VA UPS z AVR**

- Moc rozgona 650 VA
- Automatische regulacja napięcia wyjściowego (AVR)
- Kontrolka LED
- Zapobiegzenie przeciwprzepięciowe
- Ochrona odgromowa
- Alarm dźwiękowy i świetlny
- Ochrona przed przeładowaniem oraz przez całkowitym wyczerpaniem akumulatora

size: 325x139x210 mm

-  Pantone blue 072C
-  Pantone 376C
-  60% black